Cobalt Programming Wing

Cobalt® Series



GENERAL INFORMATION

Cobalt Programming Wing can be used as a facepanel remote for ETCnomad[™] (either PC or Mac) or ETCnomad Puck[™].

It can also be used as a programming surface with Remote Video Interfaces (RVI and RVI3). It cannot be used on any ETC hardware that has a dedicated facepanel nor the Congo or Cobalt Light Server. Connected devices must be running Microsoft Windows 7 or higher or Mac OS X Yosemite. The Cobalt Programming Wing is not compatible with Windows XP or earlier Microsoft operating systems. The wing provides power sensing and automatically turns on when both an active USB data connection and mains power are provided via the external in-line12V power supply.

FEATURES

- Same keypad layout as both Cobalt 20 and Cobalt 10
- Backlit keys
- Main Playback fader pair
- Four main parameter encoders with integral wheel key
- Ten backlit endless pots for Masters or Device mode
- Two DMX512/RDM ports
- MIDI In/Out
- Contact Closure Trigger
- Two Powered USB ports for connectivity
- One USB port to store and secure an ETCnomad Dongle
- One Littlite desklight connection
- VESA 100x100mm mountable
- Provides a Kensington Lock compatible locking point

INTERFACES

- AC Input 100 240VAC at 50/60Hz (via external power supply)
- Two DMX512A/RDM ports
- Three USB ports
- MIDI In/Out
- Contact Closure Trigger

ORDERING INFORMATION

Cobalt Programming Wing

PART NO.	DESCRIPTION
4370A1045-EU	Cobalt Programming Wing

Cobalt Programming Wing Accessories


PART NO.	DESCRIPTION	
4250A1022	Net3 RFR Radio Focus Remote 2.4GHz (Europe)	
4250A2026	Net3 RFR Radio Focus Remote, Receiver only	
4250A2025	Net3 RFR Radio Focus Remote, Transmitter only	
4370A1047-EU	Cobalt Motorised Fader Wing 20	
4370A1046-EU	Cobalt Motorised Fader Wing 10	
4310A1002	Universal Fader Wing 2x10 faders, Congo Blue	
4310A1003	Universal Fader Wing 2x20 faders, Congo Blue	
Tba	Cobalt Programming Wing Flight Case	
ETCnomad	ETCnomad - From 256 up to 6,144 outputs	

Ships with

- External in-line Power supply
- IEC power cords with UK13A and Schuko/NF connectors
- Dust cover
- USB cable

Compatible with

- ETCnomad on PC/Mac (Requires ETCnomad Lighting Controller Key for real-time DMX output)
- ETCnomad Puck
- RVI
- RVI3



Cobalt® Series

PHYSICAL


Cobalt Programming Wing Dimensions*


MODEL	HEIGHT	WIDTH	DEPTH
	mm	mm	mm
Cobalt PGW	116	500	341
Cobalt PGW with Flight Case	32	81	52

Cobalt Programming Wing Weights*

MODEL	WEIGHT	SHIPPING WEIGHT	
	kgs	kgs	
Cobalt PGW	4.5	7.3	

*Weights and dimensions typical





≣TC

Corporate Headquarters • 3031 Pleasant View Rd, PO Box 620979, Middleton WI 53562 0979 USA • Tel +1 608 831 4116 • Fax +1 608 836 1736 London, UK • Unit 26-28, Victoria Industrial Estate, Victoria Road, London W3 6UU, UK • Tel +44 (0) 20 8896 1000 • Fax +44 (0) 20 8896 2000 Rome, IT • Via Pieve Torina, 48, 00156 Rome, Italy • Tel +39 (06) 32 111 683 • Fax +44 (0) 20 8752 8486 Holzkirchen, DE • Ohmstrasse 3, 83607 Holzkirchen, Germany • Tel +49 (80 24) 47 00-0 • Fax +49 (80 24) 47 00-3 00 Hong Kong • Room 1801, 18/F, Tower 1 Phase 1, Enterprise Square, 9 Sheung Yuet Road, Kowloon Bay, Kowloon, Hong Kong • Tel +852 2799 1220 • Fax +852 2799 9325 Web • www.etcconnect.com • Copyright©2015 ETC. All Rights Reserved. All product information and specifications subject to change. 4370L1050-GB Rev. A 10/2015