



RDM2go

A palm-sized, multi-functional DMX/RDM tool that provides fixture addressing and testing, DMX snapshot playback, data monitoring, and cable integrity checks.

Perfect for lighting technicians, system installers, and rental house staff who need a portable, all-in-one device for on-site fixture setup, diagnostics, and troubleshooting.

- Supports DMX, RDM, and Ilumicode protocols for comprehensive fixture management.
- Offers full RDM functionality to easily address, locate, and monitor fixtures.
- Records DMX snapshots and tests cable integrity for complete system diagnostics.
- Directly addresses Iluminarc IP fixtures that lack an onboard display.
- Features a bright, easy-to-read OLED display for clear data monitoring.
- Includes a carry pouch, USB charging cable, and DMX connector adapters.

SPECIFICATIONS

Dynamic Effects

Standalone Color Mixing: Yes

Color Temperature Presets (Ilumicode): Yes

Dim Modes (Ilumicode): 5

Customizable Programs: Yes

Recall Custom Programs: Yes

Construction / Physical

Dimensions: 2.76 x 1.52 x 3.92 in (70 x 39 x 100 mm)

Weight: 0.77 lb (0.35 kg)

Exterior Color: Black

Housing Material: Aluminum die-cast

Connections

Power Input: Micro USB-B Male

Data Connectors: 5-pin XLR

Cable Length (power): 3 ft (0.91 m)

Control

Protocol(s): DMX, RDM, Ilumicode

DMX Channels: 1, 2, 3, 4, 5, 6 or 7

Modes/Personalities (Ilumicode): 13 personalities (ARC 1, ARC 1+D, ARC2, ARC2+D, ARC3, ARC3+D, ARC FULL, REMOTE, SOLID, SPECIAL1, SPECIAL2, VW, VW+D)

Electrical

Power and Current: 18 W, 0.15 A @ 120 V, 60 Hz

Power and Current: 18 W, 0.09 A @ 208 V, 60 Hz

Power and Current: 18 W, 0.08 A @ 230 V, 50 Hz

Battery

Battery type: Lithium Ion

Rechargeable: Yes

Battery Life: 8 hours

Battery Power: 3.7 V, 1,200 mAh

Certifications / Qualifications

Certifications: CE

IP Rating: IP20, dry location

Required Accessories

DMX Cables

Optional Accessories

DMX Cables

What's Included

RDM2go

Carry Pouch

2 pc, 3- to 5-pin converters

5-pin male to bare wire adaptor

USB-A Male to Micro USB-B Male (3 ft)