

MAGMA FOG 1500 IP

SPECIFICATIONS / TECHNICAL DATA

KEY FEATURES

- 1500W IP65 water-based fogger
- 60,000 CFM (cu ft/min) maximum output
- Thermally protected heat exchanger
- Intuitive DMX-512 and RDM control
- Onboard LCD touch screen
- Optional wireless and wired remotes



PRODUCT DESCRIPTION

The **MAGMA FOG 1500 IP™** is a 1500W water based, IP65 rated fog machine with a maximum output of 60,000 CFM (cu ft/min). Features include an easy-to-use onboard LCD touch screen, an intuitive DMX-512 and RDM control, and optional wired and wireless remote-control.

Each **MAGMA FOG 1500 IP** comes equipped with a thermally protected heat exchanger that has an initial warm up time of 14 minutes, with a fluid consumption rate of 6.76 oz (200 ml/min). This unit is designed with a durable aluminum housing, IP65 locking power in, IP65 locking 5pin XLR connectors (DMX In/Out), a 5-liter (1.32 gallon) tank, two heavy duty carry handles, and a hanging bracket for truss mounting.

PRODUCT SPECIFICATIONS

PERFORMANCE

- Rated Power: 1500W
- Max Output: 60,000 CFM* (cu ft/min.)
- Ready Time: Initial = 14 Minutes*
- Fluid Capacity: 1.32 gallons (5 liters)
- Fluid Consumption: 6.76 oz/min (200 ml/min)

*approximate

COMPATIBLE FLUID

Atmosity Extreme Filtered Fog Fluid (AEF-2L, AEF-4L, AEF-20L)

CONSTRUCTION

- Thermally Protected Heat Exchanger
- Rugged Case Design
- Convenient Carry Handles



MAGMATIC



MAGMA FOG 1500 IP

SPECIFICATIONS / TECHNICAL DATA

CONTROL

3 DMX Channel Modes (1 / 2 / 4)
Onboard LCD Touch Control Panel
DMX-512 and RDM Protocol Support
Optional MAGFLY Wireless DMX Transceiver
Optional MAGRF Wireless and MAGREMOTE
Wired Remotes

CONNECTIONS

Locking 5pin XLR Connector, DMX In/Out
IP65 Locking Power Connector In
With Wired Digital Communication Network

SIZE / WEIGHT

Length: 25.5 in. (648mm)
Width: 13.3 in. (337mm)
Height: 16.2 in. (411mm)
Weight: 61.3 lbs. (27.8kg)

ELECTRICAL

AC120V 60Hz (US Version)
AC230V 50Hz (EU Version)
20A @ 120VAC(NFB)
10A @ 230VAC - 240VAC
Max Power Consumption: 1600W

THERMAL

Maximum Ambient Temperature (Ta max) 104°F
(40°C)
Exterior Surface Temperature, Steady State:
149°F (65°C)

ACCESSORIES

MagFLY (MSR934) Wireless DMX Transceiver
Module
MagRF (MSR912) RF Module and Wireless
Remote

APPROVALS / RATINGS

CE | IP65



648 mm
(25.5 in.)



337 mm
(13.3 in.)

411 mm
(16.2 in.)

MAGMATIC